

CLAIMS

What is claimed is:

1. An apparatus for providing non-contact thermal measurements at high spatial and thermal resolutions, comprising:

5 an illumination source;

means for generating a signal in response to registration of the magnitude of light received from said illumination source that is reflected from the surface of an object; and

means for generating a bandwidth-limited AC-component of the signal from said illumination detector while said object is subjected to modulated thermal excitation.

2. An apparatus for providing non-contact thermal measurements at high spatial and thermal resolutions, comprising:

an illumination source;

an array of individual illumination detectors;

15 said illumination detectors configured to generate signals in response to registration of the magnitude of light received from said illumination source that is reflected from the surface of an object; and

a signal processor;

20 said signal processor configured to filter one or more direct current components from said signal while said object is subjected to modulated thermal excitation to discern a small thermorefectance signal from noise.

3. An apparatus as recited in claim 1, wherein said means for generating a signal in response to registration of the magnitude of light received from said illumination source that is reflected from the surface of an object comprises:
an array of individual illumination detectors.

5

4. An apparatus as recited in claim 3, wherein:
said array of illumination detectors is adapted to generate information on the intensity of light received by each of said individual illumination detectors in the array.

10
15
20

5. An apparatus as recited in claim 1 or 2, further comprising:
a display;
said display adapted for displaying a bandwidth-limited AC-component of the signal.

6. An apparatus as recited in claim 1 or 2, further comprising:
means for receiving a bandwidth-limited AC-component of the signal and
computing a thermal measurement based on a change in registered surface reflectance.

7. An apparatus as recited in claim 6:
wherein said object has a known thermorefectance constant; and

wherein said change in registered surface reflectance is in response to a change in the thermoreflectance coefficient of the surface material of said object resulting from a temperature change associated with said thermal excitation.

- 5 8. An apparatus as recited in claim 1 or 2, further comprising:
 means for generating a superresolution image from a combination of thermal
 images having a lower spatial resolution.
9. An apparatus as recited in claim 8, wherein said means for generating a
10 superresolution image comprises:
 a computer; and
 programming associated with said computer for,
 receiving a plurality of thermal images having a first image resolution, and
 combining said thermal images having said first resolution by interpolating
15 pixel values into a thermal image having a higher second resolution.
10. An apparatus as recited in claim 1 or 2, wherein said illumination source
 comprises a laser light source.
- 20 11. An apparatus as recited in claim 10, wherein said laser light source
 operates at wavelength ranging from approximately 500 nm to approximately 800 nm.

12. An apparatus as recited in claim 10, wherein said laser light source has a wavelength of approximately 655 nm.

13. An apparatus as recited in claim 10, wherein said laser light source has an
5 output power ranging from approximately 1 mW to approximately 100 mW.

14. An apparatus as recited in claim 10, wherein said laser light source has an output power of approximately 5 mW.

15. An apparatus as recited in claim 1 or 2, further comprising:
an x-y translation stage;
said translation stage configured to provide motion to said illumination source
and said illumination detector in relation to the surface of said object;
wherein a thermal image may be constructed from data collected during
15 scanning of the surface of said object.

16. An apparatus as recited in claim 15:
wherein said x-y translation stage comprises a piezoelectric translation stage;
wherein said translation stage provides movement resolution that is
20 approximately equal to or higher than the desired spatial resolution at which the object
is being measured.

17. An apparatus as recited in claim 1 or 2:

wherein said illumination source is configured to generate a beam spot size that approximates, or is less than, the desired spatial resolution of thermal measurement.

5

18. An apparatus as recited in claim 17, further comprising:

an inverse-filter which is applied to remove image blurring caused by an excessively large illumination spot size.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500
505
510
515
520
525
530
535
540
545
550
555
560
565
570
575
580
585
590
595
600
605
610
615
620
625
630
635
640
645
650
655
660
665
670
675
680
685
690
695
700
705
710
715
720
725
730
735
740
745
750
755
760
765
770
775
780
785
790
795
800
805
810
815
820
825
830
835
840
845
850
855
860
865
870
875
880
885
890
895
900
905
910
915
920
925
930
935
940
945
950
955
960
965
970
975
980
985
990
995

19. An apparatus as recited in claim 1 or 2, wherein said illumination detector comprises a photodiode.

20. An apparatus as recited in claim 2 or 3, wherein said array of illumination detectors comprises an array of photodetectors ranging in size from approximately 16 x 16 array to approximately 64 x 64.

21. An apparatus as recited in claim 2 or 3, wherein said array of illumination detector comprises an array of photodetectors ranging in size from approximately 2 x 2 to approximately 256 x 256.

22. An apparatus as recited in claim 1 or 2, wherein the frequency range of said modulated thermal excitation to which said object is subjected ranges from

approximately 0.1 Hz to approximately 100 kHz.

23. An apparatus as recited in claim 1, wherein said means for generating a bandwidth-limited AC-component of the signal from said illumination detector while said object is subjected to modulated thermal excitation comprises:

a signal processor;

said signal processor configured to filter one or more direct current components from said signal to discern a small thermorefectance signal from noise.

24. An apparatus as recited in claim 2 or 23, wherein said signal processor is selected from the group of narrow band filters consisting essentially of a lock-in amplifier, differential boxcar averaging circuit, and FFT analyzer.

25. An apparatus as recited in claim 2 or 23, wherein said signal processor is configured to filter out components of the signal other than a single harmonic of the registered illumination level.

26. A method as recited in claim 25:

wherein said single harmonic that is at, or associated with, the frequency of

modulation to which said object is subjected.

27. An apparatus as recited in claim 2 or 23, wherein said signal processor is configured to pass a band of frequencies that is less than approximately 10 Hz.

28. An apparatus as recited in claim 2 or 23, wherein signal processor has a
5 passband having a maximum width of approximately 1 Hz.

29. An apparatus as recited in claim 2 or 23, wherein said signal processor is configured to pass a band of frequencies that is limited to approximately 0.1 Hz.

30. An apparatus as recited in claim 1 or 2, further comprising:
an imaging device adapted to receive a portion of the reflected illumination for
aligning position of the illumination source in relation to the object.

31. An apparatus as recited in claim 30, further comprising:
a splitter configured to direct portions of said reflected illumination to said
imaging device.

32. An apparatus for thermal imaging of an object and providing a
superresolution image having a resolution exceeding the resolution of the imaging
20 optics, comprising:
means for obtaining a plurality of images shifted by $1/N$ pixel lengths, where N

is the desired increase in resolution, in the positive and negative of two planar dimensions; and

means for combining said plurality of images into one image with high resolution.

5 33. An apparatus as recited in claim 32, wherein said means for obtaining said plurality of images shifted by $1/N$ pixel lengths comprises a translation stage capable of sub pixel sized translation movements.

10 34. An apparatus as recited in claim 32, wherein said means for combining said plurality of images comprises:
a computer; and
programming associated with said computer for performing pixel interpolation in combining said plurality of images into an image having a higher resolution.

15 35. An apparatus for thermal imaging of an object and providing a superresolution image having a resolution exceeding the resolution of the imaging optics, comprising:

20 a translation stage capable of sub pixel sized translation movements and obtaining a plurality of images shifted by $1/N$ pixel lengths, where N is the desired increase in resolution, in the positive and negative of two planar dimensions; and
means for combining said plurality of images into one image with high resolution.

36. An apparatus as recited in claim 35, wherein said means for combining said plurality of images comprises:

a computer; and

programming associated with said computer for performing pixel interpolation in

5 combining said plurality of images into an image having a higher resolution.

37. An apparatus for thermal imaging of an object and providing a superresolution image having a resolution exceeding the resolution of the imaging optics, comprising:

means for obtaining a plurality of images shifted by $1/N$ pixel lengths, where N is the desired increase in resolution, in the positive and negative of two planar dimensions;

a computer; and

programming associated with said computer for performing pixel interpolation in combining said plurality of images into an image having a higher resolution.

38. An apparatus as recited in claim 37, wherein said means for obtaining said plurality of images shifted by $1/N$ pixel lengths comprises a translation stage capable of sub pixel sized translation movements.

39. An apparatus for thermal imaging of an object and providing a superresolution image having a resolution exceeding the resolution of the imaging optics, comprising:

a translation stage capable of sub pixel sized translation movements obtaining a plurality of images shifted by $1/N$ pixel lengths, where N is the desired increase in resolution, in the positive and negative of two planar dimensions;

a computer; and

programming associated with said computer for performing pixel interpolation in combining said plurality of images into an image having a higher resolution.

40. A method for providing high resolution thermal imaging of an object being subjected to thermal modulation, comprising:

illuminating an area on the surface of an object for which thermal information is desired;

detecting illumination reflected from said area; and

generating an AC-coupled bandwidth-limited signal in response to detected illumination.

41. A method as recited in claim 40:

wherein said AC-coupled signal has a bandwidth with a center at, or associated with, the frequency of modulation to which said object is subjected.

42. A method as recited in claim 40, further comprising:
resolving the AC-coupled signal into an image.

43. A method for providing high resolution thermal imaging of an object being
5 subjected to thermal modulation, comprising:

illuminating an area on the surface of an object for which thermal information is
desired;

detecting illumination reflected from said area;

generating an AC-coupled bandwidth-limited signal in response to detected
10 illumination; and

resolving the AC-coupled signal into an image.

44. A method as recited in claim 43:

wherein said AC-coupled signal has a bandwidth with a center at, or associated
15 with, the frequency of modulation to which said object is subjected.

45. A method for generating superresolution thermal images from low
resolution thermal images, comprising:

obtaining multiple thermorefective images of a first spatial resolution by micro-
20 scanning; and

combining said micro-scanned thermorefective images of a first resolution by

interpolating pixels to obtain an image of a second resolution which is higher than said first spatial resolution.

46. A method as recited in claim 45:

5 wherein sufficient sub pixel offsets are represented within said multiple thermorefective images of said first spatial resolution so that the pixel interpolation can yield the desired level of resolution enhancement.

47. A method as recited in claim 44, wherein said obtaining of multiple thermorefective images is performed by acquiring thermorefective measurements at a series of sub pixel offsets during micro-scanning.

48. A method for converting a plurality of low-spatial-resolution thermal images of a device into a superresolution thermal image having increased spatial resolution, comprising:

obtaining a plurality of images shifted by $1/N$ pixel lengths, where N is the desired increase in resolution, in the positive and negative directions of two planar dimensions; and

interpolating the pixels within said plurality of images into one image with high resolution.